



Electrical equipment for mines and quarries — Explosion-protected three-phase restrained and bolted cable coupling devices for working voltages up to and including 11 kV



AS 1299:2022

This Australian Standard® was prepared by EL-023, Electrical Equipment in Mines and Quarries. It was approved on behalf of the Council of Standards Australia on 05 August 2022.

This Standard was published on 19 August 2022.

The following are represented on Committee EL-023:

Australian Cablemakers Association

Australian Chamber of Commerce and Industry

Australian Industry Group

Aviation and Marine Engineers Association

Better Regulation Division (Fair Trading, SafeWork NSW, TestSafe)

Construction Forestry Miners and Energy Union

Department of Mines, Industry Regulation and Safety WA

Department of Regional NSW

Engineers Australia

Engineers Australia/Mining Electrical and Mining Mechanical Engineering Society

Minerals Council of Australia

National Association of Testing Authorities Australia

Resources Safety & Health Queensland

University of Newcastle

This Standard was issued in draft form for comment as DR AS 1299:2022.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting: www.standards.org.au

ISBN 978 1 76113 904 8

This is a preview. Click here to purchase the full publication.

Electrical equipment for mines and quarries — Explosion-protected three-phase restrained and bolted cable coupling devices for working voltages up to and including 11 kV

Originated as AS 1299—1973 and AS 1300—1973. Previous editions AS/NZS 1299:2009 and AS/NZS 1300:2009. Revised amalgamated and redesignated as AS 1299:2022.

© Standards Australia Limited 2022

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Australian members of the Joint Standards Australia/Standards New Zealand Committee EL-023, Electrical Equipment in Mines and Quarries, to supersede AS/NZS 1299:2009, Electrical equipment for mines and quarries — Explosion-protected three-phase restrained plugs and receptacles for working voltages up to and including 3.3 kV and AS/NZS 1300:2009, Electrical equipment for mines and quarries — Bolted explosion-protected three-phase cable coupling devices.

After consultation with stakeholders in both countries, Standards Australia and Standards New Zealand decided to develop this document as an Australian Standard rather than an Australian/New Zealand Standard.

The objective of this document is to provide requirements and guidance for explosion-protected three-phase restrained plugs, receptacles and cable coupling devices to manufacturers, users, regulatory authorities and associated interests and for use with other related Australian/New Zealand Standards and relevant mining regulations. It also is to allow for the use of existing compatible cable coupling systems and for the introduction of new non-compatible cable coupling systems.

This document differs from the previous edition in that it combines the previous AS/NZS 1299 and AS/NZS 1300 into one document (now designated AS 1299).

The terms "normative" and "informative" are used in Standards to define the application of the appendices to which they apply. A "normative" appendix is an integral part of a Standard, whereas an "informative" appendix is only for information and guidance.

Contents

Pr	етасе		i
1	Scope a	nd general	1
	1.1		
	1.2	<u>*</u>	
	1.3	Terms and definitions	
	1.4	Service conditions	
	1.5	Ratings, dimensions and colour coding	
		1.5.1 Type A	
		1.5.2 Type B	
	1.6	Marking	
2			
_		Enclosure	
	۵.1	2.1.1 Explosion protection	
		2.1.2 Ingress protection	
		2.1.3 Mounting	
	2.2	Clearance and creepage distances	
	2.3	Materials	
	2.4	Fasteners	
	2.5	Cable glands	
	2.6	Terminals	
	- 3	2.6.1 General	
		2.6.2 Conductor insertion depth	
	2.7	Contact sockets and pins	
		2.7.1 General	
		2.7.2 Materials	
		2.7.3 Construction of sockets	
		2.7.4 Location of sockets and pins	8
		2.7.5 Pins	9
		2.7.6 Self-adjusting arrangements	9
	2.8	Earthing	9
		2.8.1 General	9
		2.8.2 Phase barrier	
		2.8.3 Scraping earth contact on restrained devices	9
		2.8.4 Type B alternate earth contact	10
		2.8.5 Terminals	
		Insulation material properties	
	2.10	Operating and retaining method for restrained devices	
		2.10.1 General	
		2.10.2 Removal operation	
	0.11	2.10.3 Type B devices	
	2.11	1	
	2.12	1 5	
	2.13	•	
3	Testing		
	3.1	Categories of tests	
	3.2	Routine tests	
		3.2.1 General	
		3.2.2 High voltage test	
		3.2.3 Contact pressure test	
		3.2.4 Scraping earth contact — Restrained devices	
		3.2.5 Earth contact test — Type B restrained devices	
	3.3	Type tests	
		3.3.1 General	
		3.3.2 List of type tests — Restrained devices	14

3.3.3 List of type tests — Bolted devices	15		
3.3.4 Operating and retaining mechanism test — Restrained devices	15		
3.3.5 Cable gland (slip load) test	16		
3.3.6 Phase barrier (slip load) test			
3.3.7 Thermal endurance test	16		
3.3.8 High voltage test			
3.3.9 Contact integrity test			
3.3.10 Temperature-rise test			
3.3.11 Short-circuit (through-fault) test			
3.3.12 Earth-circuit (through-fault) test			
3.3.13 Over pressure test			
3.3.14 Partial discharge test			
3.3.15 Impulse withstand test	22		
4 Figures and dimensions — Restrained devices	23		
4.1 General			
4.2 Receptacle mounting templates	40		
5 Figures and dimensions — Bolted devices	42		
5.1 General			
5.2 Adaptor, coupler and end cover			
5.3 Adaptor mounting template	47		
Appendix A (informative) Information to be provided with enquiry or order	49		
Appendix B (normative) Properties of insulating materials	50		
Appendix C (informative) Information to be provided by the designer or manufacturer	51		
Rihlingranhy			