

IEEE Guide for Grip Test Method for Fittings of High-Temperature, Low-Sag Overhead Conductor Under Tension and Electric Current Co-Effect

IEEE Power and Energy Society

Developed by the
Transmission and Distribution Committee

IEEE Std 2870™-2022

IEEE Guide for Grip Test Method for Fittings of High-Temperature, Low-Sag Overhead Conductor Under Tension and Electric Current Co-Effect

Developed by the

Transmission and Distribution Committee
of the
IEEE Power and Energy Society

Approved 9 February 2022

IEEE SA Standards Board

Abstract: Introduced in this guide is the grip test method for fittings of high-temperature, low-sag overhead conductor with long-term operating temperature of between 90 °C and 250 °C in the co-effect of the tension and the current.

Keywords: current, grip strength, high-temperature low-sag overhead conductor, IEEE 2870, tension, test

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2022 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 31 March 2022. Printed in the United States of America.

IEEE is a registered trademark in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-8460-2 STD25256
Print: ISBN 978-1-5044-8461-9 STDPD25256

IEEE prohibits discrimination, harassment, and bullying.

For more information, visit <https://www.ieee.org/about/corporate/governance/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

This is a preview. [Click here to purchase the full publication.](#)