



JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS C 8369 : 2006

(JLA/JSA)

Photoelectric controls for public lighting

ICS 29.120.40

Reference number : JIS C 8369 : 2006 (E)

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan Luminaires Association (JLA)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently **JIS C 8369** : 1988 is replaced with this Standard.

Attention is drawn to the possibility that some parts of this Standard may conflict with a patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have technical properties. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying the patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have the said technical properties.

Date of Establishment: 1964-10-01

Date of Revision: 2006-03-25

Date of Public Notice in Official Gazette: 2006-03-27

Investigated by: Japanese Industrial Standards Committee

Standards Board

Technical Committee on Electricity Technology

JIS C 8369:2006, Second English edition published in 2006-06

Translated and published by: Japanese Standards Association
4-1-24, Akasaka, Minato-ku, Tokyo, 107-8440 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

YS/AT

Contents

	Page
1 Scope	1
2 Normative references	1
3 Definitions	1
4 Classification	2
5 Performances	3
5.1 Insulation resistance	3
5.2 Dielectric withstand voltage	3
5.3 Switching operation	4
5.4 Current consumption	4
5.5 Waterproof	4
5.6 Endurance of switching operation	5
5.7 Temperature rise	5
5.8 Delay performance	5
5.9 Noise terminal voltage	5
6 Construction and materials	5
6.1 General construction	5
6.2 Materials	7
6.3 Lead wire	7
6.4 Dimensions of PC switch	8
7 PC switch receptacle	10
7.1 Classification of (PC switch) receptacle	10
7.2 Construction of receptacle	11
7.3 Dimensions of receptacle	11
8 Tests	14
8.1 Test conditions	14
8.2 Construction	14
8.3 Insulation resistance	14
8.4 Dielectric withstand voltage	14