



JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS C 8369 : 2012

(JLA/JSA)

**Photoelectric controls for public
lighting**

ICS 29.120.40;29.130.20

Reference number : **JIS C 8369 : 2012 (E)**

Date of Establishment: 1964-10-01

Date of Revision: 2012-10-22

Date of Public Notice in Official Gazette: 2012-10-22

Investigated by: Japanese Industrial Standards Committee
Standards Board

Technical Committee on Electricity Technology

JIS C 8369:2012, First English edition published in 2014-07

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

KK/AT

Contents

	Page
Introduction.....	1
1 Scope.....	1
2 Normative references	1
3 Terms and definitions	2
4 Classification and designation of products	3
4.1 Classification	3
4.2 Designation of product.....	5
5 Performances	5
5.1 Insulation resistance	5
5.2 Dielectric withstand voltage	5
5.3 Switching operation.....	5
5.4 Current consumption	6
5.5 Waterproof property	6
5.6 Endurance of switching operation	6
5.7 Temperature rise	7
5.8 Time-delay property	7
6 Construction and material	7
6.1 General construction	7
6.2 Materials	8
6.3 Lead wire	9
6.4 Dimensions of PC switch	9
7 Receptacle	13
7.1 Classification of receptacle.....	13
7.2 Construction of receptacle	13
7.3 Dimensions of receptacle	13
8 Tests	16
8.1 Test conditions	16
8.2 Construction test	16
8.3 Insulation resistance test	16
8.4 Dielectric withstand voltage test	16
8.5 Switching operation test.....	16
8.6 Current consumption test	20
8.7 Waterproof test	20
8.8 Endurance of switching operation	20
8.9 Temperature rise test	21
8.10 Time-delay property test	22

9	Inspection	22
9.1	Type inspection	22
9.2	Acceptance inspection	22
10	Marking	22
11	Precautions on use and maintenance	23
Annex A (informative)	Check items and adequate exchange period of photoelectric controls for public lighting	25
Annex B (informative)	Notes on design of photoelectric controls for public lighting built in luminaire	27
Annex C (informative)	Method for obtaining switching illuminance of photoelectric controls for public lighting	28