



---

# UL 2557

## STANDARD FOR SAFETY

### Membrane Switches

This is a preview. [Click here to purchase the full publication.](#)

UL Standard for Safety for Membrane Switches, UL 2557

First Edition, Dated December 4, 2020

### **Summary of Topics**

***This First Edition ANSI/UL 2557 dated December 4, 2020 covers membrane switches actuated by human activity, via a membrane or sensing substrate, to operate or control appliances and electrical equipment. The membrane switch electrical rating is not to exceed 30 Vrms and power not greater than 100 VA.***

The requirements are substantially in accordance with Proposal(s) on this subject dated May 8, 2020 and July 31, 2020.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

DECEMBER 4, 2020



ANSI/UL 2557-2020

1

**UL 2557**

**Standard for Membrane Switches**

**First Edition**

**December 4, 2020**

This ANSI/UL Standard for Safety consists of the First Edition.

The most recent designation of ANSI/UL 2557 as an American National Standard (ANSI) occurred on October 5, 2020. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, and Title Page.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL's On-Line Collaborative Standards Development System (CSDS) at <https://csds.ul.com>.

UL's Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL's Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

**COPYRIGHT © 2020 UNDERWRITERS LABORATORIES INC.**

This is a preview. [Click here to purchase the full publication.](#)

No Text on This Page

## CONTENTS

### INTRODUCTION

1	Scope .....	7
2	Components .....	7
3	Units of Measurement .....	7
4	References .....	8
	4.1 Undated references .....	8
	4.2 Normative references.....	8
5	Glossary.....	9

### CLASSIFICATIONS

6	Classification of Switches .....	20
	6.1 According to the switch design.....	20
	6.2 According to the basic actuation construction of the switch .....	20
	6.3 According to the nature of supply .....	20
	6.4 According to the type of load to be controlled by each circuit of the switch .....	20
	6.5 According to the number of operating cycles.....	20
	6.6 According to the operating surface temperature of mounting.....	20
	6.7 According to the ambient temperature of the environment.....	21
	6.8 According to the flammability classification .....	21
	6.9 According to degree of protection provided by the switch against the environment.....	21
	6.10 According to the basic circuit layer construction of the switch .....	22
	6.11 According to type of disconnection .....	22
	6.12 According to the end product application of switch tail flexibility .....	22

### CONSTRUCTION

7	General .....	22
8	Graphic, Adhesive, Ink, and Embossing.....	24
9	Spacer and Adhesive .....	25
10	Dome, Cavity, and Venting .....	25
11	Circuit Crossover Material .....	25
12	Cover Materials (Dielectric Film or Coating).....	26
13	Tail Connector.....	26
14	Tail Stiffener.....	26
15	Rear Adhesive .....	27
16	Other Construction Features .....	27
17	Provision for Earthing .....	27
18	Terminals and Terminations.....	27
19	Current Carrying Parts.....	27
20	Clearance and Creepage Distances – Spacings .....	27
21	Resistance to Heat and Fire .....	28
22	Flammability Classification.....	28
23	Endurance Classification .....	28
24	Circuit Base Materials (Dielectric Layers) .....	29
25	Circuit Conductors.....	30
	25.1 General.....	30
	25.2 Conductive coating .....	30
	25.3 Silver .....	30
	25.4 External copper foil or metal cladding.....	31
	25.5 Conductor width .....	31
	25.6 Midboard conductor .....	31

25.7	Edge conductor .....	32
25.8	Maximum area diameter conductor .....	32
25.9	Adhesives for conductor bonding .....	32
25.10	Contact surface plating.....	33
25.11	Through holes.....	33
25.12	Additional conductive plating.....	33
26	Assembly Process Solder Limits.....	33
27	Manufacturing Processes.....	34
27.1	General.....	34
28	Sample Circuit Conductor Pattern.....	35

## PERFORMANCE

29	General .....	38
30	Marking Rub Durability Test.....	43
31	Earthing Test.....	43
32	Visual Inspection – Characterization Test .....	43
33	Circuit Resistance – Characterization Test.....	44
34	Capacitance – Characterization Test.....	44
35	Force Displacement Test.....	44
36	Contact Bounce Time Test (optional).....	44
37	Sensitivity / Teasing Test (optional) .....	44
38	Electrostatic Discharge (ESD) Shielding Test (optional).....	44
39	Insulation Resistance Test .....	45
40	Dielectric Strength Test (Working Voltages Less Than and Equal to 30 Vrms) .....	45
41	Dielectric Strength Test (Working Voltages Greater Than 30 Vrms) .....	45
42	Heating Test.....	46
43	Endurance Contact Closure Cycling Test.....	46
43.1	General .....	46
43.2	Electrical conditions .....	47
43.3	Temperature / environmental conditions .....	47
43.4	Actuation Test.....	47
43.5	Effects of endurance cycling .....	48
44	Protection Against Environmental and Abuse .....	49
44.1	Protection against solid foreign objects.....	49
44.2	Protection against ingress of dust.....	50
44.3	Protection against ingress of water.....	50
44.4	Submersion test (optional).....	51
44.5	Chemical/solvent exposure test (optional).....	51
44.6	Hosedown test (optional).....	51
44.7	Protection against humid conditions .....	51
45	Circuit Test Methods .....	51
45.1	General.....	51
45.2	Solder thermal shock test .....	51
45.3	Conductive paste adhesion test .....	52
45.4	Plating adhesion test (for flex tail leads that are electro plated) .....	54
45.5	Bond strength test .....	54
45.6	Delamination layer to layer resistance test .....	58
45.7	Delamination and blistering test (layer to layer) .....	58
45.8	Silver migration test (IPC).....	59
45.9	Silver migration test (ASTM F 1996) (alternate to IPC silver migration test method).....	62
45.10	Flex tail assembly creasing and bending test.....	62
45.11	Flex tail pull test .....	63
45.12	Cover material adhesion test .....	63
45.13	Ambient bend test.....	65
45.14	Cold-bend test.....	67



45.15 Repeated flexing test .....68  
45.16 Stiffener bond strength test.....71  
45.17 Connector pull test (optional) .....74  
45.18 Dissimilar dielectric materials thermal cycling test.....74  
45.19 Rear adhesion to mounting surface test (optional) .....75  
46 Surface Mount Device Test .....75  
47 Marking and Documentation.....75  
47.1 General.....75  
47.2 By marking (Ma) .....76  
47.3 By documentation (Do).....77

**Annex A – ASTM’s F1683-09**

This is a preview. [Click here to purchase the full publication.](#)

No Text on This Page